

PERFECT FOR THE FIAT DUCATO – PLATFORM CHASSIS

FlexBox DRY

- ▶ 30 mm sandwich panels
- ▶ Insulated roof fitted as standard
- ▶ Double-hinged rear doors
- ▶ Rear portal & auxiliary frame hot-dip galvanised
- ▶ LED interior lighting with motion detector
- ▶ Sliding tie-down points on the floor
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)



The FLEXBOX superstructures are checked by TÜV NORD according to Code XL.



FlexBox COOL

- ▶ 60 mm sandwich panels
- ▶ 65 mm insulated floor
- ▶ Double-hinged rear doors
- ▶ Rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King



FlexBox FREEZE

- ▶ 80 mm front wall & roof
- ▶ 65 mm side wall panels
- ▶ 120 mm insulated floor
- ▶ 85 mm double-hinged rear doors
- ▶ Rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ▶ Lighting according to German Road Traffic Regulations (StVZO)



Carrier aggregates, Konvekta, Mitsubishi and Thermo King



The FLEXBOX superstructures are certified in accordance with ATP and HACCP regulations.

PERFECT FOR THE FIAT DUCATO – PLATFORM CHASSIS

Additional accessories
and individual design
solutions on request!



FLEXBOX DRY	W/B 3450 mm (L2)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	3185 x 2035 x 2085	3685 x 2035 x 2085	3935 x 2035 x 2085
Steel construction weight in kg	630	700	735
GRP structure weight in kg	350	390	410
FLEXBOX COOL	W/B 3450 mm (L3)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	3370 x 2070 x 2065	3620 x 2070 x 2065	3870 x 2070 x 2065
Steel construction weight in kg	805	895	940
GRP structure weight in kg	535	595	625
FLEXBOX FREEZE	W/B 3450 mm (L3)	4035 mm (L4)	4035 mm (L5)
Internal Dim. (L x W x H) in mm	3070 x 2050 x 1970	3570 x 2050 x 1970	3820 x 2050 x 1970
Steel construction weight in kg	900	1000	1050
GRP structure weight in kg	600	670	705

