

PERFECT FOR THE MERCEDES-BENZ SPRINTER

FlexBox DRY

- ▶ 30 mm sandwich panels
- Insulated roof fitted as standard
- ▶ Double-hinged rear doors
- ▶ Rear portal & auxiliary frame hot-dip galvanised
- ▶ LED interior lighting with motion detector
- ▶ Sliding tie-down points on the floor
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- Lighting according to German Road Traffic Regulations (StVZO)



The FLEXBOX superstructures are checked by TÜV NORD according to Code XL.



FlexBox COOL

- ▶ 60 mm sandwich panels
- ▶ 65 mm insulated floor
- ▶ Double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- Lighting according to German
 Road Traffic Regulations (StVZO)

Carrier aggregates, Konvekta, Mitsubishi and Thermo King

FlexBox FREEZE

- ▶ 80 mm front wall & roof
- ▶ 65 mm side wall panels
- ▶ 120 mm insulated floor
- ▶ 85 mm double-hinged rear doors
- Auxiliary frame hot-dip galvanised, rear portal made of stainless steel
- ▶ LED interior lighting with motion detector
- ▶ Step with handgrip at the rear
- ▶ Plastic mudguards with dirt collectors
- ► Lighting according to German Road Traffic Regulations (StVZO)





The FLEXBOX superstructures are certified in accordance with ATP and HACCP regulations.



PERFECT FOR THE MERCEDES-BENZ SPRINTER





FLEXBOX DRY	W/B 3665 mm	4325 mm
Internal Dim. (L x W x H) in mm	3435 x 2035 x 2085	4185 x 2035 x 2085
Steel construction weight in kg	665	770
GRP structure weight in kg	370	430
FLEXBOX COOL	W/B 3665 mm	4325 mm
Internal Dim. (L x W x H) in mm	3370 x 2070 x 2065	4120 x 2070 x 2065
Steel construction weight in kg	850	985
GRP structure weight in kg	565	655
FLEXBOX FREEZE	W/B 3665 mm	4325 mm
Internal Dim. (L x W x H) in mm	3320 x 2050 x 1970	4070 x 2050 x 1970
Steel construction weight in kg	950	1100
GRP structure weight in kg	635	740